






GHL Profilux Model Comparison

Controller type	<u>ProfiLux II</u>	<u>ProfiLux II eX</u>	<u>ProfiLux Plus II</u>	<u>ProfiLux Plus II eX</u>	<u>Profilux II Light</u>	<u>ProfiLux 3</u>	<u>ProfiLux 3 eX</u>
Image							
Channels illumination control	8	8	8	8	4	32	32
1-10V-interfaces	4 (optional 8)	4	4	4 (optional 10)	4	4 (optional 32)	6 (optional 32)
Controllable sockets	24	24	24	24	4	64	64
Expansion slots	1	-	3	3	-	2	2
Dosing pump control	√	√	√	√	√	√	√
Current pump control	√	√	√	√	√	√	√
RS232	√	√	√	√	√	√	√
USB / LAN / WLAN	Optional	-	Optional	Optional	-	√ / √ / Optional	√ / √ / Optional
Alarm	Optional	Optical	Optical/acoustic	Optical/acoustic	Optisch	Optical/acoustic	Optical/acoustic
pH-value	Optional	√	√	√	-	√	√
Water temperature	Optional	√	√	√	√	√	√
Redox potential	Optional	-	Optional	√	-	Optional	√
Conductivity	Optional	-	Optional	√	-	Optional	√
Oxygen	Optional	-	Optional	Optional	-	Optional	Optional
Humidity	Optional	-	Optional	Optional	-	Optional	Optional
Air temperature	Optional	-	Optional	Optional	-	Optional	Optional
level sensors or leakage detectors	-	-	2	3	-	2	3
Probes included in delivery	-	Water- Temp.	Water- Temp.	Water- Temp.	-	Water- Temp.	Water- Temp.